



Merton Group UK Ltd

Cleaning and Hygiene Products That Don't Cost the Earth

TECHNICAL DATA SHEET

MAINTENANCE SPRAY – 0115

Penetrating – freeing oil and release additive. Rapid water repellent, also sealing out water. Can be used as a light lubricant.

- ❖ A blend of penetrating solvents, water dispersing agents and corrosion inhibitors.
- ❖ Instantly displaces all water from damp or wet components.
- ❖ Penetrates deeply to prevent moisture traps.
- ❖ Leaves a protective film to waterproof and guard against corrosion.
- ❖ Lubricates – increases efficiency of working parts.

USES:

Pre-spray electrical connections to prevent short circuiting due to water. Can even be used on damp connections to displace problem causing moisture.

Penetrates and helps free seized threads and bearings. Protects against further corrosion. Cleans grime from threads and components.

DIRECTIONS:

For cleaning applications, either spray directly onto surface and allow to penetrate and then wipe off or, for more difficult areas, use an extension tube and a more directional spray to force away grime.

N.B: DO NOT SPRAY ON SHORT CIRCUITS WHERE SPARKING IS LIKELY.

TECHNICAL SPECIFICATION:

Composition: Penetrating solvents, lubricants, dewatering agents and rust preventatives.

Appearance: Clear spray

Colour: Pale amber

Density: 0.67

Fragrance: Sweet characteristic

Stability: Two years minimum

Storage: Pressurised container

Store out of direct sunlight.

Temperature must not exceed 50 degrees.

Safety: Keep out of the reach of children.

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Keep away from sources of ignition – no smoking. Use in well ventilated areas, do not breathe vapour/spray.

