

0150 - Super Strength Graffiti Remover Aerosol

Page: 1

Compilation date: 01.02.18

Revision date: 23.09.2021

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Super Strength Graffiti Remover Aerosol 500ml

Product code: 0150 **Synonyms:** HC8163

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: FOR PROFESSIONAL AND INDUSTRIAL USE ONLY. Aerosol cleaner.

1.3. Details of the supplier of the safety data sheet

Company name: Merton Group UK Ltd

Unit 9 Foxholes Road off Golf Course Lane

Leicester

Leicestershire

LE3 1TH

Tel: 0116 271 4040 **Fax:** 0116 287 4756

Email: headoffice@mertongroup.co.uk

1.4. Emergency telephone number

Emergency tel: 0777 342 9963

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1: H317; STOT SE 3: H336; Aquatic Chronic 3: H412; Flam. Aerosol 1: H222;

-: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. May cause an

allergic skin reaction. May cause drowsiness or dizziness. Harmful to aquatic life with

long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

0150 - Super Strength Graffiti Remover Aerosol

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

P260: Do not breathe spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Haz. ingredients (label): Contains:

1-METHOXY-2-PROPANOL; PROPAN-2-OL; CITRUS TERPENE BLEND; LIQUIFIED

PETROLEUM GAS PROPELLANT

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

1-METHOXY-2-PROPANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-539-1	107-98-2	-	Flam. Liq. 3: H226; STOT SE 3: H336	50-70%

0150 - Super Strength Graffiti Remover Aerosol

Page: 3

BUTANE, <0.1% 1,3 BUTADIENE - REACH registered number(s): 01-2119474691-32-XXXX

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
PROPANE, <0	.1% 1,3 BUTADII	ENE - REACH registered number(s): 0	01-2119486944-21-XXXX	
200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
PROPAN-2-OL	- REACH registe	ered number(s): 01-2119457558-25		
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%
CITRUS TERP	ENE BLEND - RI	EACH registered number(s): 01-21194	193353-35	
227-813-5	5989-27-5	-	Flam. Liq. 3: H226; Skin Irrit. 2: H315; Asp. Tox. 1: H304; Aquatic Chronic 1: H410; Skin Sens. 1: H317	<1%
2-METHOXYPI	ROPANOL			
216-455-5	1589-47-5	-	Flam. Liq. 3: H226; Repr. 1B: H360D;	<1%

Non-classified ingredients:

TRIETHANOLAMINE - REACH registered number(s): 01-2119486482-31-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-049-8	102-71-6	-	-	<1%

STOT SE 3: H335; Skin Irrit. 2: H315;

Eye Dam. 1: H318

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to

fresh air in case of accidental inhalation of vapours. Consult a doctor in case of

complaints

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

0150 - Super Strength Graffiti Remover Aerosol

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back. Aerosol cans may explode during a fire, giving a high speed projectile.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Eliminate all sources of ignition. Cover leaking can until the discharge has stopped, before attempting cleanup operations.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Leaking material will evaporate leaving no residues. Wash the spillage site with large amounts of water.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

0150 - Super Strength Graffiti Remover Aerosol

Page: 5

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Prevent the build up of electrostatic charge in the immediate area. Keep away from direct sunlight.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

1-METHOXY-2-PROPANOL

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	375 mg/m3	560 mg/m3	-	-

BUTANE, <0.1% 1,3 BUTADIENE

UK 1450 mg/m3 1810 mg/m3 -		1450 mg	m3 1810 mg/m3	-	-	
----------------------------	--	---------	-----------------	---	---	--

PROPANE, <0.1% 1,3 BUTADIENE

		UK	Asphyxiating	Asphyxiating	-	-
--	--	----	--------------	--------------	---	---

PROPAN-2-OL

UK	400 ppm	500 ppm	-	-
----	---------	---------	---	---

CITRUS TERPENE BLEND

UK	100ppm	150ppm	-	-
			•	

2-METHOXYPROPANOL

UK 19 mg/m3 76 mg/m3 -

Non-classified ingredients:

TRIETHANOLAMINE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3 (no std.)		-	_

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

0150 - Super Strength Graffiti Remover Aerosol

Page: 6

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Solvents, mixed.

Evaporation rate: Moderate

Solubility in water: Soluble

Viscosity: Viscous

Boiling point/range°C: Not applicable. Melting point/range°C: Not applicable.

Flammability limits %: lower: 0.9 upper: 14.0

Flash point°C: -40 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >230 Vapour pressure: Not applicable.

Relative density: Not applicable. pH: Not applicable.

VOC g/I: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

0150 - Super Strength Graffiti Remover Aerosol

Page: 7

11.1. Information on toxicological effects

Hazardous ingredients:

1-METHOXY-2-PROPANOL

ORAL RAT LD50	5000 mg/kg	
---------------	------------	--

PROPAN-2-OL

ORAL	RAT	LD50	4700	mg/kg
ORAL	RBT	LD50	>2000	mg/kg
VAPOURS	RAT	4H LC50	46.5	mg/l

CITRUS TERPENE BLEND

ORL	RAT	LD50	>4400	mg/kg
SKN	RBT	LD50	>2000	mg/kg

Non-classified ingredients:

TRIETHANOLAMINE

ORL	RAT	LD50	>2	g/kg
SKN	RBT	LD50	>10	g/kg

Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

0150 - Super Strength Graffiti Remover Aerosol

Page: 8

1-METHOXY-2-PROPANOL

FISH	96H LC50	>4600	mg/l	
------	----------	-------	------	--

PROPAN-2-OL

Daphnia magna	48H EC50	>100	mg/l
FISH	48H EC50	>100	mg/l

CITRUS TERPENE BLEND

FISH	96H LC50	33	mg/l	
------	----------	----	------	--

TRIETHANOLAMINE

FISH	48H EC50	1390	mg/l
FISH	96H LC50	>5000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Soluble in water. Vapour is heavier than air.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Recycling/reclamation of metals and metal compounds.

Waste code number: 16 05 05

Disposal of packaging: Dispose of as normal industrial waste. Empty cans must not be burned because of

explosion hazard.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

0150 - Super Strength Graffiti Remover Aerosol

Page: 9

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D
Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the

formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels

in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

0150 - Super Strength Graffiti Remover Aerosol

Page: 10

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H360D: May damage the unborn child.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.