

Merton Group UK Ltd

Cleaning and Hygiene Products That Don't Cost the Earth

TECHNICAL DATA SHEET

DRY BRITE METALLISED FLOOR POLISH – 1103

Metallised polish for extreme strength and durability coupled with ease of removability.

- Produces a deep shine with excellent slip resistance without burnishing.
- Protects and prolongs the life of flooring materials.
- May be easily maintained by damp mopping.

USES:

For all linoleum, PVC, rubber, sealed cork, terrazzo and thermoplastic floors.

N.B. Not suitable for use on unsealed wood, unsealed cork or laminate flooring.

DIRECTIONS:

Dry Brite Metallised Floor Polish must be applied to a clean, grease-free floor.

Strip old polish with Floor Polish Stripper then rinse thoroughly with clean water. Allow the floor to dry.

Apply a thin, even film of the product using a clean lint-free mop or applicator. Apply a second coat when the first is dry (approximately 30 minutes).

<u>N.B</u>: If the flooring is worn or porous, apply Base Coat Floor Seal prior to polish application.

Maintenance

Damp Mopping: As required, using Lemon Floor Jell or Universal Cleaner.

Spray Cleaning/Burnishing: As required, though a daily routine with Floor Maintainer will increase the life expectancy.

Coverage

60 square metres per litre.



TECHNICAL SPECIFICATION:

Composition:	A blend of acrylic copolymers, resins and copolymer wax incorporating wetting agents and film forming aids in a stable water-based emulsion form incorporating metal cross linking additives.
	additives.

Appearance:	Translucent emulsion
Colour:	Cream
Viscosity:	< 10 cps
Density:	1.024
pH:	8.3
Activity:	15%
Fragrance:	Characteristic, slightly sweet
Stability:	Two years in an unopened container
Storage:	Protect from freezing

Safety: Keep out of the reach of children.

Safety data sheet available for professional user on request.