



Merton Group UK Ltd

Cleaning and Hygiene Products That Don't Cost the Earth

TECHNICAL DATA SHEET

SUPER HIGH SOLIDS METALLISED FLOOR POLISH - 1107

A metallised polish for extreme strength and durability coupled with ease of removability.

- ❖ Non-yellowing cross linked polymer film.
- ❖ Does not discolour even the lightest floor.
- ❖ Produces a deep shine with excellent slip resistance.
- ❖ Responds brilliantly to all spray burnishing techniques.

USES:

For all linoleum. P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors.
NB: not suitable for unsealed wood, unsealed cork or laminate flooring.

DIRECTIONS:

Super High Solids Metallised Floor Polish must be applied to a clean grease free floor. Strip old polish then rinse thoroughly with clean water, allow the floor to dry. Apply a thin even film of Super High Solids Metallised Floor Polish using a clean lint free mop or applicator. Apply a second coat when the first is dry (approx. 30 mins). May be buffed as required to enhance gloss.

COVERAGE: 60m² per litre.

MAINTENANCE: Damp mopping as required.

TECHNICAL SPECIFICATION:

Composition: An advanced blend of styrene / acrylic polymer, wax, wetting agents, film-forming agents and preservatives in a water based emulsion form incorporating metal cross linking additives.

Appearance: Thin, translucent emulsion

Colour: White

Viscosity: < 10cps

pH: 8.6

Density: 1.039

Activity: 25%

Fragrance: Characteristic slightly sweet

Stability: Two years in unopened container

Storage: Protect from freezing

Safety: Keep out of the reach of children.

Safety data sheet available for professional user on request.

